

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-280507

(43)Date of publication of application : 10.10.2001

(51)Int.Cl.

F16J 15/10
B29C 45/00
C08L 23/10
C08L 53/00
C08L 91/00
C09K 3/10
// B29K 23:00
B29K 25:00
B29L 31:26

(21)Application number : 2000-092023

(71)Applicant : BRIDGESTONE CORP

(22)Date of filing : 29.03.2000

(72)Inventor : IMAI YASUSHI
MASHITA NARUHIKO
YAMAMOTO YOSHIHIRO
SHIBATA MATSUMURA

(54) SEALING MATERIAL, MOLD FOR MANUFACTURING THE SEALING MATERIAL, AND
COMPOSITE FOR SEAL AND MANUFACTURING METHOD THEREFOR

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a composite for a seal with a low hardness and easy-to- mold sealing material, having excellent dust resistance, waterproofness or the like and superior adhesiveness to a cover member not to cause detachment and allowing use as a high-performance gasket, satisfactory in durability and adhesiveness between the seal material and the cover member.

SOLUTION: This composite for the seal has the sealing material circumferentially extending on the cover member. In section of the seal material in a direction nearly orthogonal to the extension direction of the sealing material, a portion of $(L_m/L_p) \leq 3$ is 50% or higher to the full length of the seal material, wherein L_p is a length of a contact part with the cover member, and L_m is a length of a non contact part with the cover member. Preferably, the portion of $(L_m/L_p) \leq 3$ is present evenly to the full length of the seal material, or the sealing material has a taper face.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

